

TIPPER CM 165 FLAP PFR

Can be applied to forklift trucks. Ideal for turning upside down and moving bins. Equipped as standard with a sequence valve which allows bins to be locked and turned upside down with a single command, quick hooking/unhooking and connection tubes. The innovative patented locking system adds to the originality of this tipper, equipped with adjustable forks which allow holding boxes of several sizes. The model made of stainless steel, is recommended for the foodstuffs, fish industry and butchery sectors



TECHNICAL DATA





Forks in open position.



Forks in closed position.

CM 165 FLAP PFR

Modello - Model			CM 165 FLAP PFR	CM 165 FLAP INOX PFR
A	Lunghezza - Length	mm	1450	1450
B	Larghezza - Width	mm	930	930
C	Altezza - Height	mm	750	750
D	Interasse forche - Fork base	mm	420 + 750	420 + 750
E	Altezza contenitori - Height of containers	mm	400 + 1150	400 + 1150
H	Baricentro senza carico - Barycentre without load	mm	280	280
G	Baricentro del carico - Barycentre of the load	mm	500	500
I	Spessore - Thickness	mm	350	350
Cl	Angolo di rovesciamento - Tilting angle	°	165	165
Q	Portata max. (in trasferimento) - Maximum load (during transfer)	Kg	1500	1500
-	Portata di esercizio (in rovesciamento) - Operating capacity (during tilting)	Kg	1200	1200
-	Pressione di esercizio - Operating pressure	bar	140	140
-	Peso - Weight	Kg	327	327
-	Linee idrauliche necessarie - Required hydraulic lines	n.	2 (1 leva d.e.) (1 d.c. lever)	2 (1 leva d.e.) (1 d.c. lever)
-	Forche regolabili - Adjustable forks		150x40 L=1080	150x40 L=1080



Download the form in [PDF format](#).