

FORKLIFT QUADRUPLEX CM 16QHAL

The hydraulic forklift ideal for medium powered tractors is equipped with free lifting that allows the load to be lifted 200mm without changing the overall dimensions. It is an excellent solution for all cultivation with limited access dimensions. It is made up of "U" and "H" shaped hot rolled steel proiles with steel grade ST 52.3, roller bearings, four FLEYER chains and two double extension lateral lifting cylinders that provide the operator with great visibility.



TECHNICAL DATA



Straight roller radial bearings.



"Fleyer" type lifting chains.



Hot-rolled steel sections.



Distributor with 4 levers.



Slide shift.



Forche pieghevoli e regolabili.



Free lifting.

QUADRUPLEX										
MODELLI MODELS	C mm	H mm	P Kg	B mm	A mm	L mm	T mm	E mm	D mm	Q Kg
16 QHAL 2500	2500	1280	470	1100	1950	700	250	490+720	500	1600
16 QHAL 3300	3300	1480	520	1350	2450	700	250	490+720	500	1600
16 QHAL 4000	4000	1650	580	1350	2450	700	250	490+720	500	1600

LEGENDA:

C Altezza di sollevamento
Max ground clearance

H Ingombro Max
Maximum dimensions

P Peso
Weight - Poids

B Apertura minima
Minimum opening

A Apertura Max
Maximum opening

L Larghezza elevatore
Width of forklift

T Luce piano terra
Ground clearance

E Larghezza forche
Forks width

D Baricentro del carico
Barycentre of the load

Q Portata Max
Maximum load

