

FORKLIFT TRIPLEX CM 16TC

Hydraulic forklift ideal for medium powered tractors. Maximum heights can be reached with minimum overall dimensions. It is made up of "U" shaped hot rolled steel profiles with steel grade ST 52.3, roller bearings, a FLEYER type chain and a double extension central lifting cylinder.



TECHNICAL DATA



Straight roller radial bearings.



"Fleyer" type lifting chain.



Hot-rolled steel sections.



Distributor with 4 levers.



Slide shift.



Adjustable and pliable forks.

TRIPLEX

MODELLI MODELS	C mm	H mm	P Kg	B mm	A mm	L mm	T mm	E mm	D mm	Q Kg
16 TC 2500	2500	1480	350	1100	1950	700	250	490-720	500	1600
16 TC 3000	3000	1730	395	1350	2450	700	250	490-720	500	1600
16 TC 3200	3200	1790	410	1350	2450	700	250	490-720	500	1600
16 TC 3600	3600	1930	450	1350	2450	700	250	490-720	500	1600

LEGENDA:

C Altezza di sollevamento
Max ground clearance

H Ingombro Max
Maximum dimensions

P Peso
Weight - Poids

B Apertura minima
Minimum opening

A Apertura Max
Maximum opening

L Larghezza elevatore
Width of forklift

T Luce piano terra
Ground clearance

E Larghezza forche
Forks width

D Baricentro del carico
Barycentre of the load

Q Portata Max
Maximum load

