

FORKLIFT DUPLEX CM 20DBCH

Hydraulic forklift ideal for medium and/or high powered tractors made up of "H" shaped hot rolled steel profiles with steel grade ST 52.3, roller bearings, two lateral FLEYER chains and two lateral double effect lifting cylinders that provide the operator with great visibility.



TECHNICAL DATA



Straight roller radial steel.



"Fleyer" type lifting chain.



Hot-rolled steel sections.



Distributor with 4 levers.



Slide shift FEM.



FEM forks.



Great visibility.



Lateral shift lateral pads FEM.

DUPLEX										
MODELLI MODELS	C mm	H mm	P Kg	B mm	A mm	L mm	T mm	E mm	D mm	Q Kg
20 DBCH 3200	3200	2400	690	1350	2450	800	300	240-1200	500	2000
20 DBCH 3600	3600	2600	730	1350	2450	800	300	240-1200	500	2000
20 DBCH 4000	4000	2800	770	1350	2450	800	300	240-1200	500	2000
20 DBCH 4500	4500	3050	820	1350	2450	800	300	240-1200	500	2000

LEGENDA:

C Altezza di sollevamento
Max ground clearance

H Ingombro Max
Maximum dimensions

P Peso
Weight - Poids

B Apertura minima
Minimum opening

A Apertura Max
Maximum opening

L Larghezza elevatore
Width of forklift

T Luce piano terra
Ground clearance

E Larghezza forche
Forks width

D Baricentro del carico
Barycentre of the load

Q Portata Max
Maximum load

