

FORKLIFT TRIPLEX CM 9TCL

Hydraulic forklift ideal for small or medium powered tractors. The lightness of the forklift is associated with the possibility of obtaining the maximum height with minimum overall dimensions. It is made up of "U" shaped hot rolled steel profiles with steel grade ST 52.3, roller bearings and a double extension central lifting cylinder...



TECHNICAL DATA



Straight roller radial bearing.



Standard lifting chain.



Hot-rolled steel sections.



Distributor with 4 levers.



Shift slide.



Adjustable and pliable forks.

TRIPLEX										
MODELLI MODELS	C mm	H mm	P Kg	B mm	A mm	L mm	T mm	E mm	D mm	Q Kg
9 TCL 2500	2500	1430	280	950	1800	650	200	500+620	400	900
9 TCL 3000	3000	1600	310	950	1800	650	200	500+620	400	900

LEGENDA:

C Altezza di sollevamento
Max ground clearance

H Ingombro Max
Maximum dimensions

P Peso
Weight - Poids

B Apertura minima
Minimum opening

A Apertura Max
Maximum opening

L Larghezza elevatore
Width of forklift

T Luce piano terra
Ground clearance

E Larghezza forche
Forks width

D Baricentro del carico
Barycentre of the load

Q Portata Max
Maximum load

