



## ELEVATORI IDRAULICI DUPLEX

*Duplex hydraulic forklifts*

# CM 20DBCH



**Elevatore idraulico duplex per trattori di media ed elevata potenza. Robusto e bilanciato. Offre all'operatore la massima visibilità.**

- Cuscinetti radiali a rulli cilindrici
- Due catene di sollevamento "Fleyer"
- Profili in acciaio ad "H" laminati a caldo
- Due cilindri laterali di sollevamento a doppio effetto
- Attacco a tre punti cat. 2
- Distributore idraulico a 4 leve
- Traslatore laterale tipo FEM a scorrimento su pattini in bronzo
- Forche industriali tipo FEM
- Cilindro di brandeggio con snodo regolabile
- Tubi di collegamento al trattore

***Duplex hydraulic forklift suitable to medium and high power tractors. Sturdy and balanced. Provide the operator with great visibility.***

- *Cylindrical roller bearings*
- *Two "Fleyer" lifting chains*
- *"H" shaped hot rolled steel profiles*
- *Two lateral double effect lifting cylinders*
- *Cat.2 three point linkage*
- *Distributor with 4 levers*
- *FEM side shift sliding on bronze pads*
- *FEM forks*
- *Tilting cylinder with adjustable junction*
- *Connecting hoses to the tractor*



**Cuscinetti radiali a rulli cilindrici**  
*Straight roller radial bearings*



**Catene di sollevamento tipo "Fleyer"**  
*"Fleyer" type lifting chains*



**Distributore 4 leve**  
*Distributor with 4 levers*




**Forche FEM**  
*FEM forks*



**Traslatore laterale FEM**  
*FEM side shift*



**Ottima visibilità**  
*Great visibility*



**Profili in acciaio laminati a caldo**  
*Hot-rolled steel profiles*

CM 20DBCH				
MODELLO <i>Model</i>	PORTATA <i>Load capacity</i>	ALTEZZA SOLLEVAMENTO <i>Lifting height</i>	INGOMBRO <i>Overall dimensions</i>	PESO <i>Weight</i>
	Kg	mm	mm	Kg
<b>20 DBCH 3200</b>	2000	3200	2400	690
<b>20 DBCH 3600</b>	2000	3600	2600	730
<b>20 DBCH 4000</b>	2000	4000	2800	770