



ELEVATORI IDRAULICI QUADRUPLEX

Quadruplex hydraulic forklifts

CM 20QH



QUADRUPLEX

**Elevatore idraulico per trattori di media e elevata potenza.
Minimo ingombro che consente applicazione su sollevatore anteriore.**

- Cuscinetti radiali a rulli cilindrici
- Quattro catene di sollevamento "Fleyer"
- Profili in acciaio ad "H" laminati a caldo
- Due cilindri laterali di sollevamento a doppio effetto
- Attacco a 3 punti cat. 2/3
- Distributore idraulico a 4 leve
- Traslatore laterale tipo FEM a scorrimento su pattini in bronzo
- Tubi con avvolgitore
- Forche industriali tipo FEM
- Cilindro di brandeggio con snodo regolabile
- Tubi di collegamento al trattore

Hydraulic forklift suitable to medium and high power tractors. Minimum overall dimensions.

- Cylindrical roller bearings
- Four "Fleyer" lifting chains
- "H" shaped hot rolled steel profiles
- Two lateral double effect lifting cylinders
- Cat.2/3 three point linkage
- Distributor with 4 levers
- FEM side shift sliding on bronze pads
- Connecting hoses with winder
- FEM forks
- Tilting cylinder with adjustable junction
- Connecting hoses to the tractor



Cuscinetti radiali a rulli cilindrici
Straight roller radial bearings



Catene di sollevamento tipo "Fleyer"
"Fleyer" type lifting chains



Distributore 4 leve
Distributor with 4 levers



Forche FEM
FEM forks



Traslatore laterale FEM
FEM side shift



Pattini traslatore laterale FEM
FEM side shift pads



Profili in acciaio laminati a caldo
Hot-rolled steel profiles

CM 20QH

MODELLO <i>Model</i>	PORTATA <i>Load capacity</i>	ALTEZZA SOLLEVAMENTO <i>Lifting height</i>	INGOMBRO <i>Overall dimensions</i>	PESO <i>Weight</i>
	Kg	mm	mm	Kg
20 QH 2700	2000	2700	1450	700
20 QH 3200	2000	3200	1550	750
20 QH 3600	2000	3600	1650	780
20 QH 4000	2000	4000	1750	820
20 QH 4500	2000	4500	1875	870
20 QH 5200	2000	5200	2050	960
20 QH 6000	2000	6000	2250	1160

