



## ELEVATORI IDRAULICI TRIPLEX

*Triples hydraulic forklifts*

# CM 16THAD



**Elevatore idraulico per trattori di media potenza. Dotato di alzata libera che consente di sollevare il carico senza variare l'ingombro.**

- Cuscinetti radiali a rulli cilindrici
- Quattro catene di sollevamento "Fleyer"
- Profili in acciaio ad "U" ed "H" laminati a caldo
- Cilindro di sollevamento a doppio effetto
- Attacco a tre punti cat. 2
- Alzata libera 200 mm
- Distributore idraulico a 4 leve
- Traslatore laterale a scorrimento su boccole autolubrificanti
- Forche pieghevoli e regolabili
- Cilindro di brandeggio con snodo regolabile
- Tubi di collegamento al trattore

***Hydraulic forklift suitable to medium power tractors. Equipped with free lifting for raising the load without changing overall dimensions.***

- *Cylindrical roller bearings*
- *Four "Fleyer" lifting chains*
- *"U" and "H" shaped hot rolled steel profiles*
- *Double effect lifting cylinder*
- *Cat.2 three point linkage*
- *Free lifting 200 mm*
- *Distributor with 4 levers*
- *Side shift sliding on self-lubricating bushes*
- *Adjustable and pliable forks*
- *Tilting cylinder with adjustable junction*
- *Connecting hoses to the tractor*



**Cuscinetti radiali a rulli cilindrici**  
*Straight roller radial bearings*



**Catene di sollevamento tipo "Fleyer"**  
*"Fleyer" type lifting chains*




**Distributore 4 leve**  
*Distributor with 4 levers*



**Forche pieghevoli e regolabili**  
*Adjustable and pliable forks*



**Traslatore laterale**  
*Side shift*



**Alzata libera**  
*Free lifting*



**Profili in acciaio laminati a caldo**  
*Hot-rolled steel profiles*

CM16THAD				
MODELLO <i>Model</i>	PORTATA <i>Load capacity</i>	ALTEZZA SOLLEVAMENTO <i>Lifting height</i>	INGOMBRO <i>Overall dimensions</i>	PESO <i>Weight</i>
	Kg	mm	mm	Kg
<b>16THAD 2500</b>	1600	2500	1480	390
<b>16THAD 2800</b>	1600	2800	1580	425
<b>16THAD 3000</b>	1600	3000	1650	445
<b>16THAD 3200</b>	1600	3200	1730	465
<b>16THAD 3600</b>	1600	3600	1850	510