



ELEVATORI IDRAULICI TRIPLEX

Triplex hydraulic forklifts

CM 30TBCH



**Elevatore idraulico triplex per trattori di elevata potenza.
Offre robustezza ed elevata visibilità all'operatore.**


- Cuscinetti radiali a rulli cilindrici
- Quattro catene di sollevamento "Fleyer"
- Profili in acciaio ad "H" laminati a caldo
- Due cilindri laterali di sollevamento a doppio effetto
- Attacco a 3 punti cat. 3
- Distributore idraulico a 4 leve
- Traslatore laterale tipo FEM a scorrimento su pattini di bronzo
- Forche industriali tipo FEM
- Cilindro di brandeggio con snodo regolabile
- Tubi di collegamento al trattore

***Triplex hydraulic forklift suitable to high power tractors.
Very sturdy, it provides the operator with great visibility.***

- *Cylindrical roller bearings*
- *Four "Fleyer" lifting chains*
- *"H" shaped hot rolled steel profiles*
- *Two lateral double effect lifting cylinders*
- *Cat. 3 three-point linkage*
- *Distributor with 4 levers*
- *FEM side shift sliding on bronze pads*
- *FEM forks*
- *Tilting cylinder with adjustable junction*
- *Connecting hoses to the tractor*



Cuscinetti radiali a rulli cilindrici
Straight roller radial bearings




Catene di sollevamento tipo "Fleyer"
"Fleyer" type lifting chains



Distributore 4 leve
Distributor with 4 levers



Forche FEM
FEM forks



Pattini traslatore laterale FEM
FEM side shift pads



Traslatore FEM
FEM side shift



Profili in acciaio laminati a caldo
Hot-rolled steel profiles

CM 30 TBCH

MODELLO <i>Model</i>	PORTATA <i>Load capacity</i> Kg	ALTEZZA SOLLEVAMENTO <i>Lifting height</i> mm	INGOMBRO <i>Overall dimensions</i> mm	PESO <i>Weight</i> Kg
30 TBCH 2700	3000	2700	1820	820
30 TBCH 3200	3000	3200	1985	870
30 TBCH 3600	3000	3600	2120	915
30 TBCH 4000	3000	4000	2250	960
30 TBCH 4500	3000	4500	2420	1040
30 TBCH 5200	3000	5200	2650	1130
30 TBCH 6000	3000	6000	2920	1220